SHP-TS 100W E40 SLV

Item No: 0020686


















- A range of High Pressure Soduim lamps withhigh xenon pressure boost luminous efficacy up to 150lm/w, - Long life between 24,000 and 32, 000 hours, - Strong performance and high reliability, - For use in Car park, Street and Flood lighting applications

Technical Assets

Dimensions (mm)

SHP-TS



	SHP-TS	35W	50W	70W	100W	150W	250W	400W
Ī	L	156	156	156	211	211	260	292
	D	39	39	39	48	48	48	48

Photometrics

SHP-TS 100W E40 SLV

Item No: 0020686



General data

Product name	SHP-TS 100W E40 SLV	
Technology	HID	
Watt (Rated) (W)	100	
Cap/Base	E40	
Lamp finish	Clear	
Fixture rating	Open	
General application	Logistics & Industry	
ETIM Class	EC000821	
E-number FI	4845508	
E-number SE	8358013	
E-number Norway	3824257	

Optical data

•	
Useful luminous flux (Φuse)	10500
Luminous flux (Rated) (lm)	10500
Ambient temperature for maximum luminous flux (°C)	25
Correlated colour temperature (k)	2050
CRI (Ra)	20
Colour Variation Initial (SDCM)	N/A
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable
Rated lumen maint. factor (%) at 4000 h 50Hz	96
Rated lumen maint. factor (%) at 6000 h 50Hz	94
Rated lumen maint. factor (%) at 8000 h 50Hz	93
Rated lumen maint. factor (%) at 12000 h 50Hz	91
Rated lumen maint. factor (%) at 16000 h 50Hz	90
Rated lumen maint. factor (%) at 20000 h 50Hz	89

Electrical data

Power consumption (W)	100
Wattage (W)	100
Current (A)	1.2
Primary Supply/Product voltage - min (V)	100
Primary Supply/Product voltage - max (V)	100
Control gear required	Yes
Dimmable	No
Dimming method	Mains: leading / trailing edge
Lamp Energy Label (class)	F
kWh per 1000 hours burning time	110

Lifetime data

Average life (Nominal) (h)	30000
Average life (Rated) (h)	30000
Life T90	16000
Rated survival factor (%) at 2000 h 50Hz	100
Rated survival factor (%) at 4000 h 50Hz	100
Rated survival factor (%) at 6000 h 50Hz	99
Rated survival factor (%) at 8000 h 50Hz	99
Rated survival factor (%) at 12000 h 50Hz	96
Rated survival factor (%) at 16000 h 50Hz	90
Rated survival factor (%) at 20000 h 50Hz	81

Physical data

Nominal Product Length (mm)	211
Nominal Product Diameter (mm)	48
Max. Lamp Diameter (mm) - D	48
Weight (kg)	0.12

SHP-TS 100W E40 SLV

Item No: 0020686



Packaging

Product EAN number	5410288206868
Packaging single length / height (cm)	22.5
Packaging single width (cm)	5.0
Packaging single depth (cm)	5.0
DUN14 (inner)	15410288206865
Units per outer package	12
Packaging outer length / height (cm)	28.0
Packaging outer width (cm)	23.0
Packaging outer depth (cm)	25.0

Safety data

Lamp mercury content (mg)	14.4
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Suitable for household illumination	No