




Lucalox™ XO Elliptical Diffuse LU400/XO/D/40 93296

Product information

GE Lucalox™ XO High Pressure Sodium lamps offer outstanding luminous efficacy, lumen maintenance and long life, thus reducing energy and maintenance costs.

Application areas



Street and pedestrian Å.



🕬 Commercial areas







Product data

Bulb ShapeEllipticalBulb FinishDiffuseMaximum Overall Length [mm]292Net weight per piece [g]226Gross weight per piece [g]322	
Maximum Overall Length [mm]292Net weight per piece [g]226	
Net weight per piece [g] 226	
Gross weight per piece [g] 322	
Operating position U - Universal	
Mercury Content [mg] 19.2	
Brand General Electric (GE)	

Performance data

Colour Rendering Index (CRI) [Ra]	25
Nominal correlated colour temperature (CCT) [K]	2100
Nominal lumens [lm]	54000
Rated Lumens [lm]	54810
Nominal efficacy [LpW]	135
Rated efficacy [LpW]	136
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.53
Nominal chromaticity coordinate Y	0.43
Weighted energy consumption [kWh/1000h]	443.02





Electrical data

Nominal power [W]	400
Rated power [W]	403.0
Nominal lamp voltage [V]	105
Lamp Current [A]	4.4
Design Ambient Temperature [°C]	25
Run-up time (sec)	300
Hot restart time (sec)	240
Dimming Capability	Yes
Ballast Required	Yes


Logistic data

DUN Code	00043168932967
EAN Code	0043168932967
Pack Quantity	6
Layer quantity	54 EUR, 60 UK
Layer quantity EUR	54
Layer quantity UK	60
Pallet quantity EUR (PC)	162
Pallet quantity UK (PC)	180
Outer case size	380 x 255 x 302 (mm)
Product status	Available






Lumen maintenance data



Survival data







Downloads & Links

Go to the catalog site (HTTP)

HID Lamps Spectrum Catalogue (EN) (PDF)

HPS Lucalox™ XO Lamps - Data sheet (EN) (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)